



## 550 PROFESSIONAL MASKING TAPE



### Technical data sheet

#### Description

Crepe paper coated with natural rubber adhesive used for general purpose paint applications

	Backing	Adhesive	Core
CONSTRUCTION	Saturated crepe paper	Natural rubber Synthetic Resins Plasticizers Antioxidants	Fiberboard

TECHNICAL SPECIFICATIONS		English System	International System	Procedures
	Total Thickness		5.4 mils	0.137 mm
Adhesion to Steel		24 oz/in	2.6 N/cm (270 gr-f/cm)	PSTC-101
Elongation at break		10%	10%	PSTC-131
Tensile Strength		19.6 lb/in	34.3 N/cm (3.5 kg-f/cm)	PSTC-131
Temperature Resistance (30 min)		176° F	80° C	
Color		Natural		

AVAILABLE SIZES	Lengths	30, 40, 55 (yd)**	27.4, 36.5, 50.3 (m)
	Widths	1/2, 3/4, 1, 1-1/2, 2 (in)**	

\*\* Approximate (English) measure

APPLICATIONS	Pegafan 550 is an adhesive tape ideal for masking and general purpose applications, providing good adhesion to many different surfaces. Perfect for home, workshop and office use.
--------------	--

STATEMENT OF PRACTICAL USE	Tape must be applied over surfaces which are clean, dry surface and free of grease, oil or other contaminants. After application, even pressure must be applied in order to activate the adhesive.
----------------------------	--

STORAGE CONDITIONS	It must be stored in its original packaging, in a well ventilated and low humidity area, away from direct sunlight.
--------------------	---

PLEASE NOTE	This information is based on laboratory tests conducted according to Test Methods for Pressure Sensitive Tapes (15th Edition) validated by the Pressure Sensitive Tape Council. For special applications, we recommend testing the suitability of the self adhesive tape for the designated application or use  * These tests were performed in a laboratory stove on metal surfaces.
-------------	---

December 2017

